



DRAFT REGULATIONS

HISTORIC SPORTS CAR CLUB LTD

Silverstone Circuit. Silverstone. Nr Towcester. Northamptonshire. NN12 8TN

Tel: +44 (0)1327 858400. Fax: +44(0)1327 858500.

E-mail: office@hsccl.org.uk. Web Site: www.hsccl.org.uk.

HSCC Derek Bell Trophy Series © Regulations 2024

1. SPORTING REGULATIONS - GENERAL

1.1 Title and Jurisdiction:

The HSCC Derek Bell Trophy Series © is organised and administered by The Historic Sports Car Club Ltd [HSCC Ltd] in accordance with the Motorsport UK General Regulations (incorporating the provisions of the International Sporting Code of the FIA) and these Trophy regulations.

Motorsport UK Series Permit No. RS2024/TBC Race Status: National / Interclub

1.2 Officials:

- 1.2.1 Coordinator: Donna Skipworth-Michell, c/o HSCC Ltd, Silverstone Circuit, Silverstone Nr Towcester, Northants, NN12 8TN. Tel. 01327 858400
- 1.2.2 Eligibility Scrutineers: Sue Bateman, C/O HSCC Ltd, Silverstone Circuit, Silverstone Nr Towcester, Northants, NN12 8TN. Tel. 01327 858400
- 1.2.3 Series Stewards: **TBC** c/o HSCC, Silverstone Circuit, Nr. Towcester, Northants, NN12 8TN

1.3 Competitor Eligibility:

- 1.3.1 Entrants must:
 - I be fully-paid-up members of the HSCC and
 - II be in possession of a valid Motorsport UK Entrant's Licence.
- 1.3.2 Drivers and Entrant/Drivers must:
 - I be current members of the HSCC and,
 - II be registered for the Series and
 - III be in possession of a valid Competition Motorsport UK (Racing) Licence of *minimum* National (for Formula One, Formula 5000 and 2 Litre Formula 2 Cars) or Club Licence *as a minimum* for all other categories.
 - IV Or be in possession of the highest grade of national Race licence or valid FIA International Licence, together with their ASN's written consent.
 - V *If participation in the Series requires absence from education a driver, in full time school education is required to have the approval of their head teacher and a letter stating such approval from their school in order to fulfil registration for the Series. A driver shall not take time out of their education to participate in motor sport without the prior written approval of their education establishment.



1.4 Registration:

- 1.4.1 All competitors must register for the series via the online membership registration process at www.hsc.org.uk prior to the Final Closing date for the first event being entered.
- 1.4.2 The membership year runs from 1st January to 31st December. Registrations will be accepted from 1st January in the membership year.
- 1.4.3 Registration numbers will be the permanent competition numbers for the Series for that year.

1.5 Series Events:

The HSCC Derek Bell Trophy Series will be held at the following race meetings.

Date	Circuit	Status	Org. Club
4 May	Silverstone GP Circuit	Club	HSCC
8-9 June	Donington Park	Club	HSCC
13-14 July	Brands Hatch GP	Club	HSCC
26-28 July	Oulton Park	Club	HSCC
10-11 August	Croft	Club	HSCC
12-13 October	Silverstone	Club	HSCC

1.6 Awards:

- 1.6.1 All awards are to be provided by the race organisers.
- 1.6.2 **Per race:** Awards will be given to the 1st, 2nd and 3rd overall. An award will be given to first in each class, except the Invitation Class, subject to four starters in the class.
- 1.6.3 **Presentations:** Awards are to be provided for presentation at the end of each race or at the end of the meeting presentation ceremony. Class Awards will be available either from the paddock office or at a Series co-ordinated presentation one hour after the official results have been published. Any awards not collected on the day will be forfeit.
- 1.6.4 **Series:** Series winner, 2nd and 3rd overall will receive a trophy. The highest placed finisher in each class will receive a trophy subject to 4 in class. A Hoosier trophy and a tyre bonus will be awarded on the basis of sporting achievement at the end of the year.
- 1.6.5 **Title to all trophies/awards:**
If any Provisional Results are revised after any presentations and these revisions affect the distribution of awards, the Competitors concerned must return such awards to the HSCC in good condition within 7 days.

SERIES EVENT MEETINGS & RACE PROCEDURES

1.7 Entries:

- 1.7.1 Competitors are responsible for registering correct and complete entries with the correct entry fee prior to the closing date for entries before each event.
- 1.7.2 Incorrect or incomplete entries (including Driver to be Nominated Entries) are to be held in abeyance until they are complete and correct and the date of receipt for acceptance of entry purposes shall be the date on which the Secretary of the Meeting receives the missing or corrected information or fee.
- 1.7.3 Any withdrawal of Entry or Driver/Car changes made after acceptance of any entry must be notified to the Meeting Organisers in writing.
- 1.7.4 The Entry Fee for each event shall be specified in the SRs and on the entry form.
- 1.7.5 Reserves will be listed in the Final List of Entries published with Final Instructions or in a Bulletin.



1.8 Briefings:

Organisers should notify Competitors of the times and locations for all briefings in the Final Instructions for the meetings. Competitors must attend all briefings.

1.9 Qualification/Practice:

- 1.9.1 Should any Practice Session be disrupted, the Clerk of the Course shall not be obliged to resume the session or re-run sessions and the decision of the Clerk of the Course shall be final.
- 1.9.2 Any driver who has not raced on the course in its current layout within the preceding twelve months must complete a minimum of 3 laps in the car to be raced, and in the correct session, in order to qualify.
- 1.9.3 If there is more than one race at a race meeting, the grid position for race 2 will be set by the finishing order of Race1 irrespective of any driver change.

1.10 Races:

Should any race be disrupted the Clerk of the Course shall not be obliged to resume or rerun the race .

1.11 Starts:

- 1.11.1 All cars will be released to form up on the grid prior to the start in formation as specified on the grid sheet.
- 1.11.2 The start will be via a rolling start.
The minimum Countdown procedures for a rolling start /audible warning sequence shall be:-
 - I 1 minute to start of Green Flag/Pace Lap – Start Engines/Clear Grid
 - II 30 Seconds – Visible and audible warning for start of Green Flag/Pace Lap.
 - III The cars will be led around the circuit by a Pace car for a lap (or more if specified in the Final Instructions) in a two by two formation.
 - IV If the Clerk of the Course is satisfied that the cars are in a correct formation the lights on the pace car will be extinguished and the red lights at the start line will be turned on.
 - V Competing cars must then hold their position and speed until the red lights at the Start Line are extinguished denoting the start of the race. No overtaking or changing direction of any cars is allowed prior to crossing the Start Line.
- 1.11.3 Any car removed from the grid after the one minute signal or driven into pits on Green Flag Lap shall be held in the pitlane and may start the race after the last car has passed the startline or pitlane exit, whichever is the later.
- 1.11.4 Any driver unable to start the Green Flag/Pace Lap or start is required to indicate their situation as per *Motorsport UK General Regulation Q 12.11.2*. In addition, any driver unable to maintain grid position on Green Flag Lap, to the extent that ALL other cars are ahead of them, may complete the green flag lap but MUST remain at the rear of the last row of the grid but ahead of any cars to be started with a time delay.
- 1.11.5 In the event of any starting lights failure the Starter will revert to use of the National Flag.
- 1.11.6 Should circumstances at the event change such as, but not restricted to, Track Conditions or Weather, the Clerk of the Course may change Standing Starts to Rolling Starts. When this decision is made all affected competitors will be notified at the earliest opportunity along with being advised of the number of Pace laps.



1.12 SESSION RED FLAG

Should the need arise to stop any race or practice, RED LIGHTS will be switched on at the Startline and RED FLAGS will be displayed at the Startline and at all marshals' signalling points around the circuit.

This is the signal for all drivers to cease circulating at racing speeds, to slow to a safe and reasonable pace and to return to the pit lane, during practice, and to the starting grid area, during a race, unless otherwise directed by officials

Cars may not enter the Pits unless directed to do so. Work on cars already in the pits must cease when a race is stopped. All cars in the pit lane during a red flag period must take any restart from the pit exit.

1.13 Pits, Paddock & Pitlane Safety:

- 1.13.1 **Pits & Paddock:** Competitors must ensure that the Motorsport UK, Circuit Management and Organising Club Safety regulations are complied with at all times.
- 1.13.2 **Pitlane:** The outer lane or lanes are to be kept unobstructed to allow safe passage of cars, the onus shall be on all Drivers to take all due care and respect the pit lane speed limits.
- 1.13.3 **Refueling:** May only be carried out in accordance with the *Motorsport UK General Regulation* Q12.25.1 - Q12.25.4 Regulations, Circuit Management Regulations and the Supplementary Regulations or Final Instructions issued for each Circuit / Meeting.
- 1.13.4 **Speed Limit:** Pit Lane Speed Limit will be 60 Km/h (37.2Mph). You are classed as being in the pit lane once the front wheels of the car have crossed the pit entry line and you must not exceed the Pit Lane Speed Limit until the front wheels have crossed the pit exit line. Pit lane speed limiters are permitted.
Failure to comply with the speed limit may result in the imposition of the following penalties **for each Km/h over the Pit Lane Speed Limit:**
Races: A minimum fine of £10 and/or a one-second race time penalty.

1.14 Race Finishes:

To be classified as a finisher, a car must either cross the Finishing Line or take the chequered flag in the pit lane in the interests of safety, or where a back marker has been overtaken on the winner's slowing down lap and subsequently flagged off by marshals. At circuits where such use of the pit lane represents an advantage, in terms of circuit length or speed, an appropriate time penalty will be added to the driver's race time.

After taking the Chequered Flag drivers are required to:

- I progressively and safely slow down,
- II remain behind any competitors ahead of them,
- III return to the Pit Lane Entrance/Paddock Entrance as instructed,
- IV comply with any directions given by Marshals or Officials
- V keep helmets on and harnesses done up while on the circuit or in the pitlane.

1.15 Results:

All Practice Timesheets, Grids, Race Results are to be deemed PROVISIONAL until all vehicles are released by Scrutineers after Post Practice/Race Scrutineering and/or after completion of any Judicial or Technical Procedures. (Motorsport UK General Regulation D26.3).



1.16 Timing Modules:

All cars must be fitted with a working Motorsport UK approved transponder. Failure may result in competitors not being accredited with a qualifying time or being disqualified from the result as per Motorsport UK General Regulations Q12.8.1

No electronic equipment may be placed within five metres of any official timing line and any breach of this may result in the confiscation of the equipment concerned.

1.17 Qualification Races: If any event is oversubscribed the Organising Club may, at its discretion, run Qualification Races.

1.18 Operation of Safety Car: *The safety car will be brought into operation and run in accordance with Section Q, Appendix 3 of the Motorsport UK General Regulations.*

1.19 Onboard Cameras: The use of onboard cameras is permitted, but they must be fitted and declared at scrutineering for examination. Upon request any onboard footage must be made available to Clerk of the Course and or Stewards in the event of an incident, during the event.

1.20 Data Logging

The use of data loggers that record Data for post-race analysis is accepted. The use of linked data performance loggers that supply real time information in cockpit is not permitted



2. SPECIFIC SERIES REGULATIONS

- 2.1 By registering for the Series all competitors and their associates commit to positively promote and demonstrate the Motorsport UK's Respect Code which is appended to these regulations (Appendix 1).
- 2.2 Where any reports of disrespectful conduct are judged to be well founded the Series organisers may issue warnings or require remedial actions and/or report the matter to the Series Stewards who may impose appropriate penalties which can include race bans through to Series Expulsion and referral to Motorsport UK.
- 2.3 It is imperative that we promote the safety and wellbeing of young people and adults at risk. In addition to this all participants must be aware of their behaviour and conduct at all times and abusive language and harmful behaviour will not be tolerated. Any such incidents must be reported to the Series Coordinator and/or Safeguarding Officer who will also relay the report Motorsport UK. Details of the Motorsport UK Policies and Guidelines are available at www.motorsportuk.org/resource-centre by selecting Policies and Guidelines.



3. SPECIFIC SERIES PENALTIES:

In accordance with Section C of the ***Motorsport UK General Regulations***.



4. TECHNICAL REGULATIONS:

4(1) INTRODUCTION:

Organising Club: See 6.1

The following Technical Regulations are set out in accordance with the Motorsport UK specified format and it should be clearly understood that if the following texts do not clearly specify that you can do it you should work on the principle that you cannot.

If you are in any doubt check with the Eligibility Scrutineer or Eligibility Scrutineer.

4(2) GENERAL DESCRIPTION

Eligible Cars:

The HSCC Derek Bell Trophy series is open to F1, F5000 & F2 / F Atlantic, built and raced between 1/1/67 and 31/12/79.

Plus Classes for Formula 3, Formula Ford 2000 cars built and Raced between 01/01/72 and 31/12/84 Only models with a National or International Competition history in period are eligible.

~~Formula 2 Cars built after 31/12/79 to 31/12/84 are eligible by Invitation at Organisers' discretion see Class I. Cars must be in original specification with only the addition of current safety requirements. Regardless of period specification all cars must run flat bottomed.~~

The Series Organiser may classify, reclassify or exclude any car, as per section W2.2.1 of the current *Motorsport UK General Regulations*. All cars must have current FIA papers or HSCC Vehicle Identity Forms(VIF) approved by the Registrar. The issuance of a Vehicle Identity Form does not imply confirm eligibility or acceptance into the Series.

In any issues relating to the acceptability of cars presented for a race, the Series Eligibility Scrutineer will be the Arbiter. Any such decisions shall be final.

All documentation must be available at events entered, produced at scrutineering and when required at post-event checks. Cars must at all times be entered in a presentable manner, including sponsors decals.

For the purpose of these technical regulations, the term manufacture or manufacturer refers to the manufacturer of the vehicle unless clearly specified otherwise.

Manufacturer option equipment is not permitted unless specifically stated.

Chassis is defined to mean a chassis to which bodywork and mechanical components are fixed or a monocoque bodyshell .

Class Structure

Class A Formula B/Atlantic & 1600cc Formula 2 cars which as a model competed 01/01/ 1967 – 31/12/1971.

Class B **The Ray Mallock Trophy** for Formula Atlantic cars which as a model competed between 01/01/01972 – 31/12/1979 (non ground effects)

Class C **The Brian Henton Trophy** for 2000cc Formula 2 cars which as a model competed between 01/01/1972 – 31/12/1979 (non ground effects)

Class D Cars built to conform to either Formula 2 or Atlantic regulations but without aerodynamic devices manufactured and raced after January 1967.

Class E **The Howden Ganley Trophy** for Formula 5000 cars which as a model competed pre1972

Class F **The Tony Trimmer Trophy** for Formula 5000 cars which as a model competed between 01/01/1972 – 31/12/1977

Class G **Invitation Class.** For single seater cars 1600cc - 2 Litre, built between 01/01/1972 – 31/12/1984, conforming to the period regulations for Formula 3 and Formula Ford 2000.

Class I **Invitation Class.** For Single Seater cars, of unlimited capacity, built between 01/01/67 – 31/12/79, invited at the discretion of the organisers. All classes of Invitation Cars, will run as flat bottomed.

**4(3) SAFETY REQUIREMENTS:**

All Motorsport UK General Regulations Section K safety criteria regulations apply as relevant. Items K4, K6 & 7 and K12 are not mandatory.

4(4) GENERAL TECHNICAL REQUIREMENTS & EXCEPTIONS:**4(4).1 Vehicle Identity Papers**

All vehicles must comply with their HSCC VIF and with National or International Formula regulations of period (proof of period specifications will be required). Competitors are encouraged to race their cars in as close to period specification as reasonably possible. Subject to their HSCC Identity Documents indicating otherwise, vehicles must comply with vehicle regulations Section J and K. The driver must ensure the VIF is available at scrutineering and throughout each day of each event they attend.

4(4).2 Competitors are requested to contact the HSCC if they have any questions regarding the acceptable specification of their car.**4(4).3 No modifications can be made to cars beyond those originally fitted in period beyond those contained in these regulations. (No modifications effected during a car's use in "centre seat Can-Am racing" etc...)****4(5) CHASSIS:**

As the cars HSCC VIF or FIA Identity document, or as per FIA regulations of the period. Any variation is at the discretion of HSCC.

4(6) BODYWORK:**4(6).1 As the car's HSCC or FIA Identity document.****4(6).2 Bodywork must be as originally fitted in period. Aerofoil devices may only be fitted if eligible for that category of car prior to 31.12.1979 and only then if they are as originally fitted and acceptable to modern Motorsport UK Safety Standards.****4(6).3 Bodywork MUST be of a type with proven competition history for that type of car. Competitors are strongly encouraged to retain a period livery/colour scheme.****4(6).4 Wings MUST be of a proven period design and MUST respect period dimensions for the chassis type in question. Any aerodynamic aids used on cars raced in the Series must be to dimensions and method / position(s) of fixing must be as the car type raced in period. Any deviation from such (standard arrangements for the car type) must be supported by (period) photographic evidence accompanied by submissions from manufacturer or team personnel from the period in which the car raced.****4(6).5 There is an absolute maximum rear wing height of 90cm including driver when measured from the ground for all F5000.**

For Formula 2 and Atlantic cars see table below.

Rear Wing specification for Classes A B & C

Max height from the ground	All cars	90cm
Max width	All cars	110cm
Max overhang from axle centre line	1971 cars	Period
	1972	Period
	1973	Period
	1974	Period
	1975	100cm



	1976	80cm
	1977	80cm
	1978	80cm
Max overhang from Axle centre line Formula Atlantic Cars	All cars	Period

4(7) ENGINE:

As the car's HSCC or FIA Identity Document.

The engine number should be visible, together with the original manufacturer's casting numbers on both block and head(s).

For F5000 Cars

- 4(7).1 Engines fitted should be of the same type, make and swept volume as that originally fitted. Engine maximum capacity shall be 5000 c.c. (5 litres)
- 4(7).2 Carburation or fuel injection must conform to the regulations for the category under which the car originally competed.
- 4(7).3 Fuel injection shall be allowed on Class E Cars provided evidence is available to confirm that the particular car actually ran with fuel injection during its period of competition (e.g. cars raced in the USA Formula A Championship), otherwise class E cars shall run carburetor fed engines.
- 4(7).4 Fuel injection or carburetor fed engines shall be allowed on Class F Cars.
- 4(7).5 Rev. limit for engines is free.
- 4(7).6 Exhaust systems must be to the same configuration as those used on the particular car type in its period of competition. No crossover manifolds or "2 into 1" type "balanced" systems shall be allowed.
- 4(7).7 The HSCC may permit, by individual application, the substitution of various original engines by another more readily available type, however competitors should note that the acceptance of a particular engine/chassis combination for this particular Series does not guarantee acceptance for international events.
- 5(7).8 Cast-Iron or aluminium cylinder heads are permitted.

For Formula 2 Cars

- 4(7).8 Engines fitted should be of the same type, make and swept volume as that originally fitted. However, Cosworth BDG or FVC engines are permissible substitutes for certain engines (e.g. BMW and Hart F2 engines), by individual application to the F2 registrar.
- 4(7).9 Carburation or fuel injection must conform to the regulations for the category under which the car originally competed.
- 4(7).10 Exceptionally registered substitute engines for the FVA will be allowed provided that they are of a type manufactured within the era and that the substitute engine does not change the car's category or class, typically the Ford BDA engine shall be accepted as a replacement for the FVA.
- 4(7).11 The HSCC may permit, by individual application, the substitution of various original engines by another more readily available type, however, competitors should note that the acceptance of a particular engine/chassis combination for this particular Series does not guarantee acceptance for international events.
- 4(7).12 An increase of engine capacity up to 1% over the original maximum limit to the relevant class/formula will be permitted, subject to an individual application, and approval from the Formula 2 Registrar.



4(8) SUSPENSIONS

- 4(8).1 As the car's HSCC or FIA Identity document.
- 4(8).2 All cars must run at a minimum ride height of 40 millimetres, or as per FIA or RAC period regulations.
- 4(8).3 Suspension mountings and pick-up points shall be in original positions as when the car was manufactured or the car type's competition period.
- 4(8).4 Suspension should be as originally fitted to the car or of a type for which there is proven competition use in period. Remote reservoir dampers of any type are NOT acceptable. Variable rate springs may only be used where there is proven competition use on that type of chassis in period, (rising rate suspension only allowed on cars that were originally fitted with such – e.g. Lola T400).

4(9) TRANSMISSION:

As the car's HSCC or FIA Identity document, and to period regulations.

4(10) ELECTRICS:

- 4(10).1 As the car's HSCC or FIA Identity document, and to period regulations.
- 4(10).2 Original production specification with only assisted electronic aids allowed to a retained original distributor. Electronic ignition is acceptable, ignition systems must be of the period or to a manufacturer's replacement specification.
- 4(10).3 A red warning light must be fitted (K5.)
- 4(10).4 No electronic "measuring device" (except Tacho / Rev. Counters) shall be allowed. No potentiometers, wheel sensors, data-logging of any type or description shall be allowed.
- 4(10).5 Any such data-logging / sensor system fitted to a car presented for scrutineering shall render the car ineligible for racing and the car shall be deemed as having failed scrutineering and shall not be allowed to race at that particular meeting (or any future meeting unless all system is removed).

4(11) BRAKES:

- 4(11).1 As the car's HSCC or FIA Identity document.
- 4(11).2 Hydraulic pipes may be replaced with Aeroquip or similar.
- 4(11).3 Friction material shall be free provided on steel rotors.

4(12) WHEELS/STEERING:

As the car's HSCC or FIA identity document, and to comply with period regulations. Wheel manufacture is free provided that wheel dimensions are as per original fitment for car type / model.

4(13) TYRES:

Avon A11 slick tyres as standard, optionally Hoosier R35 or R20 tyres may be used. When conditions dictate Avon wet weather tyres, of the type Avon / BMTR refer to as their Contract Historic Wet Weather Tyre in A15 Compound, may be used. For all cars classes a variation maybe permitted at the discretion of the HSCC.

4(14) WEIGHTS:

As the car's identity document, and to comply with period regulations.

All cars MUST respect the period minimum weight limit for the type of chassis and formula in period.

Class A B, and C



1971	450 Kgs
1972	450 Kgs
1973	450 Kgs 4cyl/475 6 cyl
1974	475 Kgs 4cyl/500 6 cyl
1975	500 Kgs
1976	500 Kgs
1977	500 Kgs
1978	500 Kgs
Class B All Years	440 Kgs
Class D All years	420 Kgs

4(15) FUEL TANK/FUEL:

As the car's HSCC identity documents, and to comply with period regulations.

Fuel must be in accordance with Motorsport UK General regulations Section B Nomenclature & Definitions Pump Fuel parts (a) or (b),

4(16) SILENCING:

Maximum permitted noise levels are not defined in these series regulations. However, some circuits/venue owners/meeting organisers may impose restrictions in the Supplementary Regulations. The HSCC will give as much advanced warning as possible of the need for cars to comply with any noise restriction.

4(17) NUMBERS AND DECALS:

- 4(17).1 Numbers must be displayed as per Section J4 and drawing 4 of the *Motorsport UK General Regulations*. It is a competitor's responsibility for the competing vehicle to be easily identified by all course officials.
- 4(17).2 Individual sponsor's decals are limited to two per vehicle dimensions and limitations as per sections H27 and H28 of the *Motorsport UK General Regulations*.
- 4(17).3 All competing cars must display at least two HSCC badges one on each side of the car, together with series or race sponsor stickers as required. Failure to display the required stickers by an individual competitor may result in grid or race penalties being applied.
- 4(17).4 Individual advertising as per *Motorsport UK General Regulations* H28.1.1 – H28.1.6

5(18) ~~Geoff Lees Class Technical Regulations~~

~~The Geoff Lees Classes are open to Formula 2, Formula Atlantic, Formula 3, Formula Ford 2000 and Formula Super Vee (Water Cooled) cars built and raced between 1/1/79 and 31/12/89. Cars must be in original specification with only the addition of current safety requirements. Cars should have a current FIA Historic Technical Passport (HTP) or an HSCC Vehicle Information Form (VIF) as proof of conformity.~~

5(18).1 ~~SAFETY REQUIREMENTS:~~

~~All Motorsport UK Section K safety criteria regulations apply as relevant. Regulations K4, K6 & 7 and K12 are not mandatory.~~

5(18).2 ~~GENERAL TECHNICAL REQUIREMENTS & EXCEPTIONS:~~

~~———— All vehicles must comply with their HSCC VIF and with National or International Formula regulations of period (proof of period specifications will be required). Competitors are encouraged to race their cars in as close to period specification as reasonably possible.~~



Only models with a National or International Competition history in period are eligible.

Subject to their HSCC VIF indicating otherwise, vehicles must comply with Motorsport UK Regulations Sections J and K

Competitors are requested to contact the registrar or any member of the Series Technical Committee if they have any questions regarding the acceptable specification of their car.

In any issues relating to the acceptability of cars presented for a race, the Series Eligibility Scrutineer will be the Arbiter. Any such decisions shall be final.

~~5(18).3 CHASSIS:~~ As the car's HSCC VIF or FIA HTP, or as per FIA or National regulations of the period. Any variation is at the discretion of the Series Technical Committee.

~~5(18).4 BODYWORK:~~ Exactly as the car's HSCC VIF or FIA HTP.

Bodywork must be as originally fitted in period.

Bodywork MUST be of a type with proven competition history for that type of car. Competitors are strongly encouraged to retain a period livery/colour scheme.

Wings MUST be of a proven period design and MUST respect period dimensions for the chassis type in question. Any aerodynamic aids used on cars raced in the Series must be to dimensions and method / position(s) of fixing must be as the car type raced in period. Any deviation from such (standard arrangements for the car type) must be supported by (period) photographic evidence accompanied by submissions from manufacturer or team personnel from the period in which the car raced.

No part of the car may be lower than the main monocoque floor.

~~5(18).5 ENGINE:~~ As the car's HSCC VIF or FIA HTP.

For Formula 2 Cars

Engines fitted should be of the same type, make and swept volume as that originally fitted. However, Cosworth BDG or FVC engines are permissible substitutes for certain engines (e.g. BMW and Hart F2 engines), by individual application to the HSCC Office.

Carburation or fuel injection must conform to the regulations for the category under which the car originally competed.

The organisers may permit, by individual application, the substitution of various original engines by another more readily available type, however, competitors should note that the acceptance of a particular engine/chassis combination for this particular Series does not guarantee acceptance for international events.

An increase of engine capacity up to 1% over the original maximum limit to the relevant class/formula will be permitted, subject to an individual application, and approval from the HSCC Office.

For Formula Atlantic Cars
Either Ford BDA or BDD engines will be accepted.

~~2000cc:~~ The only engines permitted are units having a maximum capacity of 2000cc and of a type used in period and in a chassis permitted to be used.

All cars will have an induction system which must be of original specification and can be either mechanical or electronic injection. All air feeding the engine must pass through a throttling flange of 3mm minimum length, and having a parallel hole of 24mm diameter maximum. The airbox must be of the original pattern as used in the period and be constructed of material as used in period. A jig will be used to fit over the existing airbox. It is prescribed that the entire inlet system, including manifolds, injectors or carburettors, airbox and restrictor must fit into a box of 1m long by 110mm wide by 150mm high. The total airbox system must be capable of sustaining a vacuum of 5" Hg (mercury) when using a pump drawing a maximum of .9cfm of free air.



Formula Ford 2000

The only permitted engine is the Ford NE series 2 Litre SOHC with 2 Venturi carburettors with nominal bore 90.84mm + 0.5mm rebores allowance and stroke 76.95mm. Production tolerances are permitted providing the total swept volume does not exceed 2025cc. Engines will be mounted upright and aligned fore and aft in the chassis.

Formula Super Vee

The permitted engine must have a maximum displacement of 1600cc made from standard VW components of series production in the VW Golf, Scirocco or Passat.

~~5(18).6~~ — **SUSPENSION:** As the car's HSCC or FIA Identity document.

~~Ground Clearance:~~

~~The minimum ride height for all cars applies at all times through a Competition and testing for compliance may take place at any time during a Competition, including when the Competitor is seated, stationary in the~~

~~car, with fuel and fluids. All cars must pass a simple ground clearance test to show a minimum ride height of 40mm at all times during a Competition. No entirely sprung part of the car may be less than 40mm from the ground with the car stationary, in its normal racing trim, and with the Competitor on board.~~

~~Apart from the complete front and rear wheels, no part of the car shall systematically or continuously touch the ground when the car is in motion. Any device bridging the space between the bodywork and the~~

~~ground is prohibited. Any device fitted to the car to lower its ground clearance whilst in motion, and/or any component (including "helper springs" which are of a lower spring rate to the spring they are intended to "help") which has that same effect is forbidden.~~

~~Suspension mountings and pick-up points shall be in original positions as when the car was manufactured or the car type's competition period.~~

~~Suspension should be as originally fitted to the car or of a type for which there is proven competition use in period. Remote reservoir dampers to period specification (or of an equivalent design where original specification dampers are no longer available) are permitted. Subject to regulation 19.17.1 above, variable rate springs may only be used where there is proven competition use on that type of chassis in period.~~

~~5(18).7~~ — **TRANSMISSION:** As the car's HSCC VIF or FIA HTP, and to period regulations.

~~5(18).8~~ — **ELECTRICS:** As the car's HSCC VIF or FIA HTP, and to period regulations.

~~Original production specification with only assisted electronic aids allowed to a retained original distributor. Electronic ignition is acceptable, ignition systems must be of the period or to a manufacturer's replacement specification. Ignition timing must be set by the distributor — no "mapping" of electronic timing systems is permitted unless used in period in that model.~~

~~A red warning light must be fitted (Motorsport UK Regulation K5.)~~

~~5(18).8~~ — **BRAKES:** As the car's HSCC VIF or FIA HTP.

~~Hydraulic pipes may be replaced with Aeroquip or similar.~~

~~Friction material shall be free provided on steel rotors.~~

~~5(18).9~~ — **WHEELS/STEERING:** As the car's HSCC VIF or FIA HTP, and to comply with period regulations.

~~Wheel manufacture is free provided that wheel dimensions are as per original fitment for car type / model.~~

~~5(18).10~~ — **TYRES:** Avon A11 slick tyres as standard, optionally Hoosier R35 or R20 tyres may be used. When



~~conditions dictate Avon wet weather tyres, of the type Avon / BMTR refer to as their Contract Historic Wet Weather Tyre in A15 Compound, may be used. For all cars classes a variation maybe permitted at the discretion of the HSCC.~~

~~5(18).11 — **WEIGHTS:** As the car's HSCC VIF or FIA HTP, and to comply with period regulations.~~

~~5(18).12 — **FUEL TANK/FUEL:**~~

~~(a) **Tank:** As per the FIA Regulations to comply with period regulations.~~

~~(b) **Fuel:** As FIA Regulation Appendix J Art 252. Art 9~~

~~5(18).13 — **SILENCING:** Maximum permitted noise levels are not defined in these series regulations. However, some circuits/venue owners/meeting organisers may impose restrictions in the Supplementary Regulations. The HSCC will give as much advanced warning as possible of the need for cars to comply with any noise restriction.~~

~~5(18).14 — **NUMBERS AND DECALS: Positions**~~

~~As per Motorsport UK Yearbook Section J4 and drawing 4. Individual sponsor's decals are limited to two per vehicle. All competing cars must display at least two HSCC badges one on each side of the car. If at any time the Series has a sponsor — sponsors decals when provided must be displayed (one each side of car) failure to comply may result in grid or race penalties being applied. Individual advertising as per Motorsport UK Regulations H28.1.1 — H28.1.6~~

5. FOR FORMULA 3 & FF2000 SAFETY REQUIREMENTS:

The following Articles of Motorsport UK Section K Safety Criteria Regulations will apply: - K1; K3.1; K1.3.2; K2. & K2.1.4 Six Point; K3.2; Section K Appendix 1, Table 3, K4; K5; K6 -13

Section **(K5)**: A rearward facing red warning light is mandatory and must comply with this regulation.

• GENERAL TECHNICAL REQUIREMENTS AND EXCEPTIONS:

- All cars prior to being accepted and registered by the HSCC must comply with these Regulations and the provisions of the Regulations. Anything outside this must be approved by the eligibility scrutineer. Only very minor modifications to original specifications are permitted.
- Competitors must always make prior application to the Series Registrar in writing with reference to the unavailability of original pattern parts, panels etc. Each such case and application will be considered by the Series Organisers and the Eligibility Scrutineer and ruled thereon. Failure to comply may result in rejection of the car.
- All vehicles must comply with their HSCC or FIA Identity Documents; subject to their Identity Documents indicating otherwise, vehicles must comply with Technical Regulations for competitors (Section Q Technical).

• Engine Seals

In case of official protest all engines shall have provision for sealing as listed:

All engines must have provision for scrutineer's wire seals. 1/16in holes pre-drilled in readily accessible locations on installed engines must be available:

Sump - two holes through the cylinder block/sump joint flange, specifically a pair, on each side or diagonally opposite.

Cam Cover - at least two retaining screw heads must be cross drilled

Cam Timing Pulley - retaining bolt must be cross drilled

Inlet Manifold - at least two retaining bolt heads to the cylinder head must be cross drilled.



Carburettor - at least two retaining nuts to the cylinder head must be cross drilled

Bell housing - at least two retaining bolts to the engine must be cross drilled to enable clutch and flywheel to be adequately sealed OR competitors must be prepared to remove either engine or transmission to enable sealing of clutch and flywheel in which case at least two clutch cover retaining bolts must be cross drilled. Failure to comply renders the engine ineligible.

- **CHASSIS:**

- **1600cc:** Any chassis manufactured before 31.12.73 and of a type raced in 1600cc Formula 3 between 1.1.71 and 31.12.73.
- **2000cc:** Any chassis manufactured before 31.12.84 and of a type raced in 2000cc Formula 3. 1985 Model cars, raced in 1984 as prototypes are prohibited. A case example is the Ralt RT30 which is prohibited. Furthermore, all carbon chassis cars are prohibited though the Anson SA4 Aluminium chassis with carbon panel is acceptable.
- No modifications, other than those in §••••, are permitted without the specific approval of the Eligibility Scrutineer.
- **FF2000:** Cars must conform with the Technical Regulations of the Historic FF2000 Championship run by the HSCC

- **BODYWORK:**

- Bodywork must be as that originally fitted to the car. No modifications are permitted without the specific approval of the Eligibility Scrutineer.
- The rear wing and the method of mounting must be as original.
- The use of composite materials using carbon and/or Kevlar reinforcement is prohibited.
- Enclosure of the sides of the engine or the use of any undertray under the engine bay is prohibited even if these items were a "period" modification.
- Specifically, for 2000cc Formula 3 ground effect cars built between 01.01.1981 and 31.12.1984 the addition of a flat bottom as per the following construction and fixation methodology is mandatory. The valid year of specification will be as featured on the Historical Technical Passport first page, the HSCC VIF form or the FFSA VIF form, and will serve as reference.

Between the rear edge of the complete front wheels and the front edge of the complete rear wheels, all sprung parts of the car visible from directly beneath the car must lie on one plane within a tolerance of (+/-) 5mm. Dimensions as per the technical drawing below:

All these parts must produce a uniform, solid, hard, rigid (no degree of movement in relation to the body/chassis unit), impervious surface, under all circumstances. The periphery of the surface formed by these parts may be curved upwards with a maximum radius of 5 cm-no diffuser are permitted.

- Any specific part of the car influencing its aerodynamic performance.

Must comply with the rules relating to bodywork,

Must be rigidly secured to the entirely sprung part of the car (rigidly secured means not having any degree of movement)

Must remain immobile in relation to the sprung part of the car,



- Any device or construction that is designed to bridge the gap between the sprung part of the car and the ground is prohibited under all circumstances.
- No part having an aerodynamic influence and no part of the bodywork may under any circumstances be located below the geometrical plane generated by the plane surface provided by this article.
- **In respect of 1600cc** cars it is permitted to update the bodywork of a particular chassis to that used by the same manufacturer up to and including the last 1600cc Formula 3 race in 1973 (e.g., a March 713 may have March 733 bodywork). However, it should be understood that bodywork not originally fitted to the chassis may invalidate HSCC and/or FIA Vehicle Identity Documents.

- **ENGINE:**

- **Permitted Modifications**

1600cc: The engine block and cylinder head castings with machining completed shall be those of an engine equipping a road car model of which the series production was at least 5000 units annually. The original engine block and cylinder head may be modified freely by removal of material. The addition of material is specifically excluded. However, it is permitted to sleeve an engine that was not originally fitted with sleeves. The type of crankshaft bearings shall not be modified (e.g., the replacement of a plain bearing by a roller bearing is forbidden).

2000cc: The only engines permitted are units having a maximum capacity of 2000cc and of a type used in period and in a chassis permitted to be used. Development engines or accessories (i.e., programmable electronic ignition) developed prior to 31.12.84 for use after 31.12.84 are not permitted. As an example, this will be a VW engine with the extra- long intake manifold developed by Speiss for electronic fuel injection, even if the engine has been converted to mechanical injection.

FF2000 Engine specifications as per the Historic FF2000 Regulations issued by the HSCC

ENGINE SEALING: Moved to 5(4)

- **Engine Location** as per original.
 - **Oil/Water/Cooling** system is free, but the water-cooling radiator/s must remain in its original location.

- **Induction Systems**

1600cc: The induction system is free, but it shall mandatorily be fitted with a throttling flange of 3mm in length and with a parallel orifice of 21.5mm diameter. Through this restrictor all the air feeding the engine must pass. The restrictor shall be made of metal or metallic alloy. The airbox must be of the original pattern as used in the period and be constructed of material as used in period. A jig will be used to fit over the existing airbox. It is prescribed that the entire inlet system, including manifolds, injectors or carburetors, airbox and restrictor must fit into a box of 1m long by 110mm wide by 150mm high. No supercharging device shall be allowed even if a series production one was fitted to the original engine. The total induction system must be capable of holding a vacuum of 3in Hg (mercury) as tested on the Classic Formula 3 Association pump.

2000cc: The induction system must be of original mechanical injection type. All electronic injection systems are prohibited even if some were tested in 1984 - they have to be mechanical injection. All air feeding the engine must pass through a throttling flange of 3mm minimum length and having a parallel hole of 24mm diameter maximum. The airbox must be of the original pattern as used in the period and be constructed of material as used in period. A jig will be used to fit over the existing airbox. It is prescribed that the entire inlet system, including manifolds, injectors or carburetors, airbox and restrictor must fit into a box of 1m long by 110mm wide by 150mm high. The total airbox system must be capable of sustaining a vacuum of 5" Hg (mercury) when using a pump drawing a maximum of .9cfm of free air.



All cars: Action to be taken in the event of any car failing to achieve between 50% and 100% of the relevant vacuum readings which will be at the sole discretion of the eligibility scrutineer/registrar

- **EXHAUST SYSTEMS**

The exhaust system and manifold are free, within Vehicle Regulations.

- **IGNITION SYSTEMS**

1600cc: Ignition systems are free except electronic engine management systems are excluded.

2000cc: The ignition system must be as originally fitted; management systems are not allowed.

Distributors are free providing they retain the original drive and location. The distributor is defined as the component which triggers the LT current and distributes the HT ignition current. The ignition timing may only be varied by vacuum and/or mechanical means. It is prohibited to use any other method or component to trigger, distribute or time the ignition. It is permitted to mount a simple indicating pointer to the engine to facilitate the timing of the distributor with respect to the crankshaft/flywheel

- **FUEL DELIVERY SYSTEMS**

Only the standard mechanical fuel pump for the engine is permitted. Fuel pipes are free. Fuel cooling radiators are permitted, within safety regulations, but must be mounted within the main chassis frame.

- **SUSPENSIONS**

- Suspension as original. Remanufactured or replacement suspension components shall be dimensionally as original, but material thickness may be changed in the interests of safety.
- The suspension shall utilise only the original pick-up points unless these were modified and used on the chassis and raced in a Formula 3 1600cc race prior to 31.12.73 and 2000cc prior to 31/12/80.
- No modification permitted without consultation and ratification by the Eligibility Scrutineer.
- The use of any additional anti squat/anti droop devices is strictly prohibited.
- Dampers shall be of the same type in terms of appearance as originally fitted to the car and shall be mounted to the original mounting points. Remote reservoirs or any form of external control system are excluded. The use of more than one spring per corner is prohibited.
- Minimum wheelbase: 2000mm
Minimum track: 1200mm

TRANSMISSION:

- **1600cc:** The gearbox and differential casings shall be those of a car manufactured in at least 5,000 units in 12 consecutive months of a model recognised by the FIA, but not necessarily the model from which the engine has been taken.
- **2000cc:** Gearbox and final drive must be of the type originally fitted to the car. Torsen and Quaife differentials are strictly forbidden for all cars.
- **FF2000:** The gearbox must not contain more than four forward gears and include an operable reverse gear, capable of being engaged by the driver whilst normally seated. The ratios are free
- Torque biasing, limited slip and locked differentials are prohibited. Non-ferrous differential components prohibited.



- **ELECTRICS:**

- Batteries must be of a type which does not leak acid if inverted. The location is free.
- The engine must be fitted with an operable electric starter motor (compressed air starters are prohibited).
- The electrical system shall be fitted with a safety cut out switch as per K8 Motorsport UK Technical Regulations.

- **BRAKES:**

- The braking system must be as that originally fitted to the car.
- No modifications are permitted without the specific approval of the Eligibility Scrutineer.

- **WHEELS/STEERING:**

- Wheels should comply with current FIA Appendix J for Formula 3.
- Centre lock wheel retaining nuts must be fitted with safety ('R') clips and painted in a bright colour. Aircraft type self-locking nuts are not acceptable as an alternative.
- Wheels may be constructed from aluminium alloys or magnesium alloys.
- Note: Competitors are reminded that alloy/mag wheels can have a tendency to crack, especially the older ones. For safety reasons, please keep a check on your wheels.
- Rim dimensions:

Front 13" dia x 8.5" wide maximum: Rear 13" dia x 10" wide maximum.

FF2000 13in diameter wheels with maximum front rim width 6in and rear 8in are the only wheels permitted Material is free providing it is metal.

- Aerodynamic plates are expressly forbidden.

- **TYRES:**

- All cars use the same type and compound of Avon control tyres. Only the following tyres are permitted: For all cars classes a variation maybe permitted at the discretion of the HSCC.

2000 F3

AVON

Dry Front	7.5/210 x 13	spec no 7342 A37
Rear	9.2/220 x 13	spec no 7343 A37
Wet Front	7.5/210 x 13	spec no 7277 A27
Rear	9.2/220 x 13	spec no 7278 A27

1600 F3

AVON

Dry Front	7.5/210 x 13	spec no 7342 A37
Rear	9.2/220 x 13	spec no 7343 A37
Wet Front	7.5/210 x 13	spec no 7277 A27
Rear	9.2/220 x 13	spec no 7278 A27

FF2000 As HSCC FF2000 Championship Regs

The use of tyre heating/heat retention devices, tyre treatments and compounds is prohibited.



- A maximum of twelve Dry weather tyres per car per season ONLY are permitted by F3 or by URS FF2000 cars in the URS Trophy. Each competitor is required to complete a form indicating the tyre numbers that are going to be used at each race. The completed form must be handed to the scrutineers when the car is being scrutineered. Failure to do so could prevent a scrutineering ticket being issued. The Chief Scrutineer will monitor the tyres used and advise if the maximum number is exceeded.

- **WEIGHTS:**

Weight is the weight of the vehicle as it finishes the qualifying and/or races but excludes the driver and his equipment.

1600cc: The weight of the car shall not be less than 420kg

2000cc: The weight of the car must not be less than 440 kgs for cars built prior to 31.12.79. or 455 kgs for cars built between 01.01.80 and 31.12.84.

FF2000: The weight of the car shall not be less than 440kg for cars built up to 31.12.83

- **FUEL TANK / FUEL:**

- The fuel tank should be located in the same position as that originally fitted to the car. On safety grounds, it may be relocated subject to approval by the Eligibility Scrutineer.
- Fuel tank capacity is free.
- Fuel must be in accordance with Motorsport UK regulations Section B Nomenclature & Definitions Pump Fuel parts (a) or (b).
- **FF2000:** Tanks outside the chassis frame must comply with FIA Spec/FT3 Inboard tanks, covered externally with fireproof coating, are acceptable for events of less than 70km.

A metal tank coated with GRP does not comply

Maximum capacity 41 litres unless carried in FIA Spec/FT3 tank.

- **SILENCING:**

- 1.1 All vehicles must comply with Motorsport UK Regulation J5.17 and are also subject to individual circuit requirements if specified in Supplementary Regulations. i.e., 108db
- 1.1.1 FF2000: A mandatory silencer, Ford part no: 9095317 must be fitted and must comply with Motorsport UK Regulation J.5.17.

- **NUMBERS AND SERIES DECALS:**

- Numbers must be displayed as per Section J4 and Appendix 1 Drawing 4 of the Motorsport UK General Regulations. It is a competitor's responsibility for the competing vehicle to be easily identified by all course officials ..
- Individual sponsor's decals are limited to two per vehicle. Individual advertising as per Motorsport UK Regulations H28.1.1 – H28.1.6
- All competing cars must display at least two HSCC badges one on each side of the car, together with Series or race sponsor stickers as required. Failure to display the required stickers by an individual competitor may result in the withholding of Series points and corresponding awards.



5. APPENDICES

The following Commercial Undertakings are not subject to the Judicial procedures of either the Series Stewards and/or the Motorsport UK /MSC

5.1 Race Organising Clubs and Contacts

HISTORIC SPORTS CAR CLUB: Silverstone Circuit, Silverstone, Towcester, Northants, NN12 8TN
(T) 01327 858400 (F) 01327 858500 email: office@hsc.org.uk
Website: www.hsc.org.uk

Series Chairman: Mike Bainbridge

Series Registrar: Terry Jacob



APPENDIX 1

A socially-minded standard of behaviour is expected from everyone within the motorsport community.

By participating in a Motorsport UK event in any capacity you agree to follow the values of the Respect Code:

Motorsportuk.org/racewithrespect
#RaceWithRespect

The Values

- | | | |
|-------------|----------------|--------------|
| • Respect | • Integrity | Self-Control |
| • Fair play | • Good Manners | |

I pledge to #RaceWithRespect and:

- Contribute to a welcoming and friendly environment that ensures the safety and welfare of all participants.
- Always behave with integrity and uphold fairness in the sport; play your part in keeping the sport safe through your actions
- Treat everyone with respect, regardless of their gender, ethnic or social background, language, religious or other beliefs, disability, sexual identity or other status
- Recognise that we all represent the sport and therefore have a duty to be polite and respectful to all staff, officials, fellow competitors, volunteers, as well as fans and supporters
- Respect the rules, regulations and authority of the officials and Motorsport UK

Any breach of these obligations may result in disciplinary action.